

MOREPOWER

+3% Positive Tolerance

Positive tolerance on label rating power provides higher kWh for money invested.



Low iron, anti reflective coated glass gives 2% Energy gain.



Matching gives 2% additional power gain measured at STC conditions.



Independently verified by Photon and Öko-Test as amongst the best kWh/kWp output worldwide.



EL screening provides defect free modules.



Long life in marine and high pollution environments.



Pre-approved with financial institutions and rapid capability ensures customers' cost of project is reduced.



Audited controls for high value consistency.

FOR LONGER

True Linear Warranty 25 years

Highest power warranty coverage available on a linear basis.

Workmanship Warranty 12 years

12 years global workmanship warranty.

Strength 5400Pa

Industry leading snow loading capacity.

Degradation Resistance

Superior resistance to PID.

Low Carbon Footprint

One of the lowest carbon footprints over 100 years life cycle.

Green Credentials

Fully committed to recycling during production and end of product life, a dedicated member of PV cycle.

Eco Friendly Packaging

Friendly materials choice with high density packing.

ISO14001 accredited ISO

Continuous improvement in reducing environmental impact.



MUCH SAFER

AND GREENER

ISO9001
ISO14001
OHSAS18001



Electrical Data (STC)

Module Type	ECO-325P	ECO-330P	ECO-335P	ECO-340P	ECO-345P
Maximum Power at STC - P_{mp} (W)	325	330	335	340	345
Open Circuit Voltage - V_{oc} (V)	45.60	45.80	46.00	46.20	46.70
Short Circuit Current - I_{sc} (A)	9.19	9.28	9.35	9.44	9.45
Maximum Power Voltage - V_{mp} (V)	37.20	37.40	37.60	37.80	38.00
Maximum Power Current - I_{mp} (A)	8.73	8.83	8.91	8.99	9.08
Module Efficiency STC- η_m (%)	16.80	17.00	17.30	17.50	17.70

STC: Irradiance 1000 W/m² module temperature 25°C AM=1.5

Electrical Data (NOCT)

Module Type	ECO-325P	ECO-330P	ECO-335P	ECO-340P	ECO-345P
Maximum Power at STC - P_{mp} (W)	242	246	249	252	255
Open Circuit Voltage - V_{oc} (V)	42.60	42.70	42.90	43.10	43.30
Short Circuit Current - I_{sc} (A)	7.47	7.57	7.58	7.60	7.62
Maximum Power Voltage - V_{mp} (V)	34.50	34.60	34.90	35.00	35.20
Maximum Power Current - I_{mp} (A)	7.02	7.11	7.14	7.21	7.24

NOCT: Irradiance 800 W/m² ambient temperature 20°C wind speed :1m/s

Maximum Ratings

Maximum System Voltage (V)	1000 DC/1500 DC
Maximum Series Fuse Rating (A)	15

Temperature Ratings

Pmax Temperature Coefficient	-0.41 %/°C
Voc Temperature Coefficient	-0.32 %/°C
Isc Temperature Coefficient	+0.050 %/°C
Operating Temperature	-40~+85 °C
Nominal Operating Cell Temperature (NOCT)	44±2 °C





Mechanical Data

External Dimensions	1960x 992 x 40 mm
Weight	22.6 kg
Solar Cells	Polycrystalline 156.75 x 156.75 mm (72pcs)
Front Glass	3.2 mm tempered glass, low iron
Frame	Anodized aluminium alloy
Junction Box	IP65/IP67
Output Cables	4.0 mm ² , cable length:1100 mm
Connector	MC4 Compatible
Mechanical Load	5400 Pa

Packing Configuration

Container	40'HG
Pieces per Pallet	27
Pallets per Container	24
Pieces per Container	648

I-V&P-V Curve (ECO-330P)



* All Dimensions in mm